

Copy and use this page to record your console settings.

GL2800M

16 MIX WEDGE / IEM MONITOR CONSOLE

Grid of 16 channels (1-16) for IEM monitoring. Each channel includes:

- Gain: +48V, POLARITY, PAD, GAIN knob, HPF (2000 Hz).
- EQ: HF, LM, LF knobs, EQ IN checkbox.
- Mix: STEREO, MONO, WEDGE, IEM, M1, M2, M3, M4, M5, M6, M7, M8, M9, M10, M11, M12, M13, M14, M15, M16.
- Mute: MUTE checkbox, DIM knob.
- PFL: PFL +6 dB SIG, PFL knob.

Grid of 16 channels (1-16) for WEDGE monitoring. Each channel includes:

- Gain: +48V, POLARITY, PAD, GAIN knob, HPF (2000 Hz).
- EQ: HF, LM, LF knobs, EQ IN checkbox.
- Mix: STEREO, MONO, WEDGE, IEM, M1, M2, M3, M4, M5, M6, M7, M8, M9, M10, M11, M12, M13, M14, M15, M16.
- Mute: MUTE checkbox, DIM knob.
- PFL: PFL +6 dB SIG, PFL knob.

Global settings and auxiliary controls:

- PHONES, TALKBACK MIC, TALKBACK, OSC/NOISE, PINK NOISE, 1MHz OSC, ON/OFF, EXT TB, LATCH, TALK, GLOBAL SETTINGS.
- MUTE GROUPS: M1, M2, M3, M4.
- MIX 1-8: POST PRE, MONO, STEREO, WEDGE, IEM.
- MIX 9-12: POST PRE, MONO, STEREO, WEDGE, IEM.
- MIX 13-16: POST PRE, MONO, STEREO, WEDGE, IEM.
- PFL TRIM: MIN, MAX, FOLLOW, IEM.
- POWER: ON/OFF.
- L IEM R: WEDGE, PFL ACTIVE, MONO, PFL, EXT IN, EXT ON, EXT OFF, MUTE.
- IEM and WEDGE: Volume faders.

