

3M 4CORE 24/0.2 SCREENED CABLE

A&H PART No: AH2721

Stripped 2.5cm at both ends

PIN CONNECTIONS

1.	+V		BROWN
2.	nc		
3.	-V		BLUE
4.	0V	EARTH	SCREEN ¹
5.	0V	AUDIO	GRN/YEL
6.	nc		
7.	nc		
8.	nc		
9.	nc		
10.	PP	+48V	BLACK


nc = Not Connected

CABLE GROMMET

A&H PART No: AK2798

inserted from inside
connector housing.


REAR VIEW




10PIN FEMALE PLUG
HIROSE JR21PK-10S
A&H PART No: AL8101

10PIN MALE PLUG
HIROSE JR21PK-10P
A&H PART No: AL8102

REAR VIEW



ISSUE	REVISION	BY	DATE	NOTES	DRAWING TITLE	 ALLEN & HEATH KERNICK INDUSTRIAL ESTATE PENRYN CORNWALL TR10 9LU TEL 01326 372070 FAX 01326 377097	RG267	
1	ORIGIN	IMcB	6/9/96	TOLERANCES: +/-2.00mm	RPS11		DRAWING No M002-223 SHEET	ISSUE 3 A4
2	PRODUCTION	IMcB	12/9/96	note 1: TWIST AND INSULATE SCREEN BRAID WITH H15	DC CABLE ASSEMBLY			
3	NEW PART NUMBER	IMcB	2/10/96	NEOPRENE SLEEVE AND SOLDER DIRECT TO CONNECTOR PIN.	STOCK CODE 002-223			